

AGRILINE 4T 10W30

This is a low viscosity engine oil for gasoline and diesel engines. It combines good fluidity at low temperature with low ash content, while maintaining excellent detergent and dispersant properties.

APPLICATIONS

Used for the lubrication of light gasoline and diesel engines, which prefer this viscosity class. Particularly suitable for 4T- auxiliary engines and horticulture material (e.g. Honda).

FEATURES

Total engine protection : good engine protection and cleanliness.

Temperature stability : adequate viscosity stability.

SPECIFICATION LEVEL

ACEA	A2	API	SJ/CF
ACEA	B2	JASO	MA

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.879
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	71.7
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	11.1
Viscosity index	ASTM D2270		146
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	6.3
Pour point	ASTM D6892	°C	-33
CCS viscosity at -25°C	ASTM D5293	mPa.s	6500
Sulfated Ash	ASTM D874	Mass %	0.7
Flash Point COC	ASTM D92	°C	215

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

CHAMPION®